



GinShiCel MH512C-S-P

Technical Data Sheet

Product description

It is a high viscosity grade hydroxypropyl methyl cellulose ether that can be delayed in water to form a transparent solution. Mainly suitable for stone paint, colorful paint and other texture coatings, latex paint and other single or two component liquid building materials coating field.

Performance

It can quickly disperse in water without clumping. Different bonding time can improve the intersolubility of excipients

With good wettability, improve the adhesion between the base

Provide excellent water retention performance to ensure full operation time

Thickening effect is obvious, giving excellent suspension function, anti settlement, no stratification

With good thixotropy and leveling, anti splash, anti flow hang, improve construction

Product index

Appearance: white or almost white powder

Viscosity (BK,2%,20°C)/mpa·s: 58000-62000

Ash content /% : ≤5.0

Screen residue (180μm standard screen)/% : ≤8.0

Package specification

Composite woven bag lined with plastic film or kraft paper, 25kg/bag.

Storage and transportation

Storage and transportation should be carried out in a cool and dry place, sealed and packaged.

The product is susceptible to moisture. In the case of high temperature and high humidity, it is necessary to prevent moisture and pressure to avoid agglomeration or caking.

If the product is not used up, the packaging must be tightly sealed to prevent the intrusion of moisture.

Shelf life

It can be stored for 2 year under the condition of storage and transportation.If the product exceeds the shelf life, it can only be used after testing and verification.

Note: All the data and suggestions provided above are our reference opinions based on our understanding of current raw materials and applied technology, Since the quality of raw materials, production process, actual construction requirements and use environment adopted by users cannot be controlled, our company does not imply any guarantee and commitment to the quality of users' end products! The user is responsible for the adjustment of the formula system and the final control of quality according to the actual situation.