



GinShiCel 133-ALX new

Technical Data Sheet

Product description

It is a modified hydroxypropyl methyl cellulose ether that builds up viscosity quickly. Mainly used in tile adhesive, internal and external wall putty, all kinds of cement-based mortar and other fields.

Performance

Offers ample open time and excellent water retention
It has good wettability, so that the mortar and the bottom layer are fully bonded
Excellent operability and workability
Ensure that the mortar has a certain anti-slip function

Product index

Appearance: white or off-white powder
Viscosity (BK, 2%)/mpa·s: 35000-45000
Drying loss rate/%: ≤6.0

Package specification

Composite woven bag lined with plastic film or kraft paper, 25kg/bag.

Storage and transportation

Storage and transportation should be carried out in a cool and dry place, sealed and packaged.
The product is susceptible to moisture. In the case of high temperature and high humidity, it is necessary to prevent moisture and pressure to avoid agglomeration or caking.
If the product is not used up, the packaging must be tightly sealed to prevent the intrusion of moisture.

Shelf life

It can be stored for 2 year under the condition of storage and transportation.If the product exceeds the shelf life, it can only be used after testing and verification.

Note: All the data and suggestions provided above are our reference opinions based on our understanding of current raw materials and applied technology, Since the quality of raw materials, production process, actual construction requirements and use environment adopted by users cannot be controlled, our company does not imply any guarantee and commitment to the quality of users' end products! The user is responsible for the adjustment of the formula system and the final control of quality according to the actual situation.