



GinshiCel MB-SA-350

Technical Data Sheet

Product description	MB-SA-350 is a new type of stabilizer specially developed for fluid mortar, which is composed of special polymer materials. Recommended for gypsum-based/cement-based self-leveling mortar, grouting material, press slurry and repair mortar, etc.
Performance	Excellent water-locking performance, effectively reducing the bleeding and segregation of mortar; Mobility mortar mixing water has good versatility; Reduce the oil slick on the surface of the mortar, so that the mortar has a flat surface; The loss of fluidity over time of fluid mortar is small; Improve the later strength of mortar, reduce dry shrinkage, and improve crack resistance.
Product index	Appearance: white powder Bulk density/g/L: 800-1000 Loss on drying/%: ≤5.0
Package specification	Composite woven bag lined with plastic film or kraft paper, 25kg/bag.
Storage and transportation	Storage and transportation should be carried out in a cool and dry place, sealed and packaged. The product is susceptible to moisture. In the case of high temperature and high humidity, it is necessary to prevent moisture and pressure to avoid agglomeration or caking. If the product is not used up, the packaging must be tightly sealed to prevent the intrusion of moisture.
Shelf life	It can be stored for 1 year under the condition of storage and transportation.If the product exceeds the shelf life, it can only be used after testing and verification.

Note: All the data and suggestions provided above are our reference opinions based on our understanding of current raw materials and applied technology, Since the quality of raw materials, production process, actual construction requirements and use environment adopted by users cannot be controlled, our company does not imply any guarantee and commitment to the quality of users' end products! The user is responsible for the adjustment of the formula system and the final control of quality according to the actual situation.