



GinShiCel MHC401

Technical Data Sheet

Product description	Is a low viscosity grade hydroxypropyl methyl cellulose ether, can be quickly adhered. It is mainly used in grouting material, support mortar, grouting agent, various cement-based/gypsum based self-leveling mortar and other mobile mortar system.
Performance	Endows mortar with excellent suspension function, anti settlement, no bleeding Ensure excellent flow performance and surface smoothness of mortar With good wettability, so that mortar and the bottom fully bonded, not stratified Provide good water retention performance, reduce mortar shrinkage
Product index	Appearance: white or almost white powder Viscosity (BK ,2%,20°C)/mpa·s: 320-480 Ash content /% : ≤5.0 Screen residue (180μm standard screen)/%: ≤8
Package specification	Composite woven bag lined with plastic film or kraft paper, 25kg/bag.
Storage and transportation	Storage and transportation should be carried out in a cool and dry place, sealed and packaged. The product is susceptible to moisture. In the case of high temperature and high humidity, it is necessary to prevent moisture and pressure to avoid agglomeration or caking. If the product is not used up, the packaging must be tightly sealed to prevent the intrusion of moisture.
Shelf life	It can be stored for 2 year under the condition of storage and transportation.If the product exceeds the shelf life, it can only be used after testing and verification.

Note: All the data and suggestions provided above are our reference opinions based on our understanding of current raw materials and applied technology, Since the quality of raw materials, production process, actual construction requirements and use environment adopted by users cannot be controlled, our company does not imply any guarantee and commitment to the quality of users' end products! The user is responsible for the adjustment of the formula system and the final control of quality according to the actual situation.