



GinShiCel MH 336-RT2

Technical Data Sheet

Product description MH 336-RT2 is a modified hydroxypropyl methyl cellulose ether that builds up viscosity quickly. It is mainly used in various mortars such as interior and exterior wall putty, ceramic tile adhesive, thermal insulation mortar and masonry/plastering mortar and other types of mortar.

Performance MH 336-RT2 is a modified hydroxypropyl methyl cellulose ether that builds up viscosity quickly. It is mainly used in various mortars such as interior and exterior wall putty, ceramic tile adhesive, thermal insulation mortar and masonry/plastering mortar and other types of mortar.

Product index Appearance: white or off-white powder
Viscosity (BK,2%,20°C)/mpa·s : 45000-55000
Loss on drying /%:≤6.0
Sieve residue (180μm standard sieve)/%: ≤8.0

Package specification Composite woven bag lined with plastic film or kraft paper, 25kg/bag.

Storage and transportation Storage and transportation should be carried out in a cool and dry place, sealed and packaged.
The product is susceptible to moisture. In the case of high temperature and high humidity, it is necessary to prevent moisture and pressure to avoid agglomeration or caking.
If the product is not used up, the packaging must be tightly sealed to prevent the intrusion of moisture.

Shelf life It can be stored for 1 year under the condition of storage and transportation.If the product exceeds the shelf life, it can only be used after testing and verification.

Note: All the data and suggestions provided above are our reference opinions based on our understanding of current raw materials and applied technology, Since the quality of raw materials, production process, actual construction requirements and use environment adopted by users cannot be controlled, our company does not imply any guarantee and commitment to the quality of users' end products! The user is responsible for the adjustment of the formula system and the final control of quality according to the actual situation.