



GinShiCel MB-IP05

Technical Data Sheet

Product description	It is a comprehensively modified admixture masterbatch specially developed for general interior wall putty.
Performance	Putty batch scraping is soft and smooth, the surface is smooth and shiny, less needles Putty is plastic, scraping is brittle, does not stick to the knife, easy to polish Can be scraped thick, not thinning, reduce the number of batches Has excellent water retention and wettability, improves bond strength
Product index	Appearance:white or slightly yellow powder Drying loss rate/%:≤ 6.0 Bulk density/g/L:400-600
Package specification	Composite woven bag lined with plastic film or kraft paper, 25kg/bag.
Storage and transportation	Storage and transportation should be carried out in a cool and dry place, sealed and packaged. The product is susceptible to moisture. In the case of high temperature and high humidity, it is necessary to prevent moisture and pressure to avoid agglomeration or caking. If the product is not used up, the packaging must be tightly sealed to prevent the intrusion of moisture.
Shelf life	It can be stored for 1 year under the condition of storage and transportation.If the product exceeds the shelf life, it can only be used after testing and verification.

Note: All the data and suggestions provided above are our reference opinions based on our understanding of current raw materials and applied technology, Since the quality of raw materials, production process, actual construction requirements and use environment adopted by users cannot be controlled, our company does not imply any guarantee and commitment to the quality of users' end products! The user is responsible for the adjustment of the formula system and the final control of quality according to the actual situation.